

# Check list according to DIN EN 179



Check list emergency exit systems for replacement requirements or according to DIN EN 179

Replacement for old AP versions or AP without requirement profile (as previously ordered)

Emergency exit locks according to DIN EN 179

KFV locks can be exclusively installed in connection with certified door-lock fittings of the companies Hoppe (series 138) as well as HEWI (series 111, 114, 161, 163 und 171) Updated 09.2004.

## Versions emergency exit locks

- AS-23 00-EE     AS-2500-EE     AS-2600-EE  
 AS-23 72-EE     AS-2502-EE     AS-2602-EE

## Version mortise door lock

- RR-49-EE

## Available backset in mm:

- 30/92/9 only RR-49     55/72/9  
 35/92/9     65/72/9  
 40/92/9     80/72/9  
 45/92/9  
 50/92/9 only AS  
 55/92/9  
 65/92/9  
 80/92/9 only AS

## Available face plate versions in mm:

- F 16 x 3 only AS  
 F 20 x 3  
 F 24 x 3  
 P6 x 22 x 6  
 P6 x 24 x 6

Standard face plate colour: stainless steel.

## Dimensions versions available for emergency door locks:

- B001     B002     B003     B004

For dimensions see the "Emergency and panic door locks" brochure

## Area of application

- Wood     Euro-groove     Rebate: \_\_\_\_\_     4 mm air gap/ axis dimension: \_\_\_\_\_  
 uPVC     Profile: \_\_\_\_\_     Frame no.: \_\_\_\_\_     Door sash no.: \_\_\_\_\_  
 Aluminium     Profile: \_\_\_\_\_     Frame no.: \_\_\_\_\_     Door sash no.: \_\_\_\_\_

## Main striker:

- latch opening not adjustable or     prepared for electrical door opener (delivered with assembled latch receiver as a standard)

## DIN-direction:

- Left     Right

Please specify the door thickness: \_\_\_\_\_ mm

Additional strikers are generally **not** adjustable!!!!

**Accessories colour:** zinc-plated or stainless steel (depending on the profile)

\_\_\_\_\_  
Company stamp/date/signature